INDUSTRIAL COMPONENT DATA

Q 1,5/3A50/13-M20KU-ESA 1640731 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/3A50/13-M20KU-ESA



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 1,5/3A50/13-M20KU-ESA
Catalog number	1640731
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-FA89EAF9AB
Generated	2026-11-19

Product Overview

Panel feed-through
QUICKON wall pass-through, for outdoor wall mounting with 50 cm long conductors, 3 poles.
QUICKON panel feed-through, for the front wall assembly with 50 cm long wires, 3-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Technical dataProduct propertiesProduct type Panel feed-through
Number of positions 3
Position marking 1, 2, 3
Number of connections 3
Number of connections per position 1
Shielded no
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Connection dataConnection technology
Connection method On the device side Single wires
Frequency of connections between conductors of the same cross section 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)

Conductor connection
Conductor cross section flexibel 0.75 mm² ... 1.5 mm²
Conductor cross section solid 0.75 mm² ... 1 mm²
Connection cross section AWG 18 ... 16
Tightening torque Union nut 2.5 Nm
Tightening torque Contact carrier 3.75 Nm
Tightening torque Locking nut 3.75 Nm
Wrench size Union nut 24 mm
Wrench size Contact carrier 24 mm
Pin assignment
Contact Color (signal designation) Contact (optional) 1 BN
2 WH
3 BU
DimensionsDimensional drawing
Width 24 mm
Height 24 mm
Length 42.7 mm
Electrical propertiesRated surge voltage (III/3) 6 kV
Contact resistance < 3 m?
rated voltage (II/2) 630 V (with insulating sleeve)
rated voltage (III/2) 320 V (with insulating sleeve)
Rated voltage (III/3) 250 V (with insulating sleeve)
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 17.5 A
Material specificationsColor (Housing) green (RAL 6021)
Material Housing PA
Flammability rating according to UL 94 V0
Material wire insulation PVC / PE
Contact material Copper alloy
Contact surface ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/3A50/13-M20KU-ESA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.