INDUSTRIAL COMPONENT DATA

Q 1,5/3L90/13KU-DSI 1670413 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/3L90/13KU-DSI



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 1,5/3L90/13KU-DSI
Catalog number	1670413
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-B932E6217A
Generated	2026-11-19

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1670413
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 19 (PC-2002)
GTIN 4017918153199
Weight per Piece (excluding packing) 25.580 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Color green
Locking type Screw locking

Connection method QUICKON connection
Dip-solder connection
Note on the internal connection method The product must be screwed to the PCB before soldering. Self-tapping screws in acc. with ISO 1481-ST 2,9 x 6,5 C.
Number of positions 3
Wrench size, union nut 24 mm
Tightening torque, union nut 2.5 Nm
Wrench size, contact carrier 24 mm
Tightening torque contact carrier 3.75 Nm
Tightening torque, counter nut 3.75 Nm
Number of connections 3
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 16
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 Cl.2-5, min. wire diameter 0.2 mm
Wire insulation material PVC / PE
Wire diameter including insulation >= 3 mm
Position marking 1, 2, 3
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 80 °C
-25....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/3L90/13KU-DSI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.