INDUSTRIAL COMPONENT DATA

# Q 1,5/4A15/24-M20KU-ESA BK PE 1403470 PHOENIX CONTACT Panel feed-through Q 1,5/4A15/24-M20KU-ESA BK PE 14034..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/4A15/24-M20KU-ESA BK PE**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | Q 1,5/4A15/24-M20KU-ESA BK PE |
| Catalog number | 1403470 |
| Category | Sensor-actuator connector chassis |
| Minimum order | 50 Pcs |
| Document ID | EO-63711B6456 |
| Generated | 2026-11-19 |

## Product Overview

Panel feed-through - Q 1,5/4A15/24-M20KU-ESA BK PE - 1403470
Feedthrough, with 1.5 mm² wire outlet and 0.15 m braided wire, connection thread: M20, 4 poles

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |

## Additional Product Information

Panel feed-through with 1.5 mm² wire output and 0.15 m litz wire, connecting thread: M20, 4-pos.
Key Commercial Data
Orderkey 1403470
Packing unit 1
GTIN 4046356654807
Custom tariff number 85444290
General
Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Length of cable 0.1 m
Color black
Connection method QUICKON connection

Single litz wires 10 cm long; 1.5 mm²
Note on the internal connection method Pos. 1: black; pos. 2: brown; pos. 3: gray; pos. 4: green/yellow
Number of positions 4
Wrench size, union nut 19 mm
Tightening torque, union nut 3 Nm
Wrench size, contact carrier 24 mm
Tightening torque contact carrier 4.5 Nm
Tightening torque, counter nut 4.5 Nm
Number of connections 4
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 1 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 16
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm
Wire insulation material PVC / PE
Wire diameter including insulation >= 1.8 mm ... 3 mm
External cable diameter 6 mm ... 12 mm
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -40 °C ... 80 °C (specifications of the cable manufacturer must also be observed)
-25 °C ... 50 °C (when the conductor is connec...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/4A15/24-M20KU-ESA BK PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.