

INDUSTRIAL COMPONENT DATA

QUINT4-PS/1AC/24DC/2.5/PT 2909576 PHOENIX CONTACT

Power supply unit

Brand: PHOENIX CONTACT | Manufacturer Part Number: QUINT4-PS/1AC/24DC/2.5/PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	QUINT4-PS/1AC/24DC/2.5/PT
Catalog number	2909576
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-84BFC8FDAB
Generated	2026-09-21

Product Overview

Power supply unit

Primary switching power supplies, QUINT POWER, Push-in connection, Rail mounting, input:1phase, output: 24 VDC / 2.5 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Power Supplies (PS)**

Additional Product Information

Key Commercial Data

Orderkey 2909576

Packing unit 1 pc

GTIN 4055626356495

Weight per Piece (excluding packing) 311.100 g

Custom tariff number 85044030

Country of origin DE (Germany)

Dimensions

Width 32 mm

Height 106 mm

Depth 90 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -25 °C ... 70 °C (> 60 °C Derating: 2.5 %/K)
Ambient temperature (start-up type tested) -40 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)
Climatic class 3K3 (in acc. with EN 60721)
Degree of pollution 2
Installation height ≤ 5000 m (> 2000 m, observe derating)
Input data
Input voltage range 100 V AC ... 240 V AC -15 % ... +10 %
110 V DC ... 250 V DC -20 % ... +40 %
Dielectric strength maximum 300 V AC 30 s
Discharge current to PE < 0.25 mA (264 V AC, 60 Hz)
Current consumption 0.85 A (100 V AC)
0.7 A (120 V AC)
0.39 A (230 V AC)
0.37 A (240 V AC)
Nominal power consumption 71 VA
Inrush surge current typ. 10 A (at 25 °C)
Mains buffering typ. 54 ms (120 V AC)
typ. 54 ms (230 V AC)
Input fuse 3.15 A (slow-blow, internal)
Type of protection Transient surge protection
Protective circuit/component Varistor
Output data
Nominal output voltage 24 V DC
Setting range of the output voltage (USet) 24 V DC ... 28 V DC (constant capacity)
Nominal output current (IN) 2.5 A
Static Boost (IStat.Boost) 3.125 A (≤ 40 °C)
Dynamic Boost (IDyn.Boost) 5 A (≤ 60 °C (5 s), Input

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QUINT4-PS/1AC/24DC/2.5/PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.