
INDUSTRIAL COMPONENT DATA

RBO 12-4L-HC 3076061 PHOENIX CONTACT Bolt connection terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RBO 12-4L-HC



Manufacturer	PHOENIX CONTACT
MPN / Reference	RBO 12-4L-HC
Catalog number	3076061
Category	Feed-through terminal block
Minimum order	2 Pcs
Document ID	EO-FC8EC48295
Generated	2026-11-18

Product Overview

Bolt connection terminal block
Stud terminal block, nominal voltage: 1500 V, nominal current: 415 A, number of connections: 8, connection type: Stud connection, 1st floor, Dimensioning cross-section: 240 mm², mounting class: NS 35/7.5, NS 35/15, direct screwing, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3076061
Packing unit 2 pc
Minimum order quantity 2 pc
Note Made to Order (non-returnable)
GTIN 4055626311203
Weight per Piece (excluding packing) 860.000 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 8

Potentials 4
Nominal cross section 240 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 13.78 W
Maximum load current 415 A (with 240 mm² conductor cross section)
Nominal current IN 415 A
Nominal voltage UN 1500 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Note regarding shock protection Touch proofness is effective only if the ring cable lug is insulated with a shrink sleeve and does not extend beyond the cover.
Result of surge voltage test Test passed
Surge voltage test setpoint 12 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.7 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of tight fit on support Test passed
Tight fit on carrier NS 35
Setpoint 20 N
Result of voltage-drop test Test passed
Requirements, voltage drop <= 3.2 mV
Result of temperature-rise test Test passed
S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RBO 12-4L-HC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.