INDUSTRIAL COMPONENT DATA

RC-09S2N122000 1596547 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-09S2N122000



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-09S2N122000
Catalog number	1596547
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-F739F9FD15
Generated	2026-11-18

Product Overview

Device connector, front mounting
M23, Conect. plug. to be apar. front wall, RC, straight, shielded: yes, Screw lock, No. of poles: 8+1, Direction of rotation: Opposite movement, contact type: Female, Weld connection, Flat joint, 4x Ø2.7, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242901
M23, Device connector front mounting, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 8+1, Direction of rotation: Counter direction, contact connection type: Socket, Solder cup, Flat gasket, 4x Ø 2.7 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connectors (device side)
ConnectorInsulating body
Coding N
Insertion/withdrawal cycles 50
Connection method Solder cup
Contact switching type Socket
Application Signal
Number of positions 9
Direction of rotation Counter direction

Connection profile 8+1
Contact diameterPower contacts 2 mm
Litz wire cross-sectionPower contactsmin. 0.08 mm²
Litz wire cross-sectionPower contactsmax. 2.5 mm²
Rated currentPower contacts 20 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Contact diameterSignal contacts 1 mm
Litz wire cross-sectionSignal contactsmin. 0.08 mm²
Litz wire cross-sectionSignal contactsmax. 1 mm²
Nominal current per signal contact 8 A
Housing
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-09S2N122000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.