INDUSTRIAL COMPONENT DATA

RC-12P1N8A4100 1597488 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-12P1N8A4100



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-12P1N8A4100
Catalog number	1597488
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-97FFE93A61
Generated	2026-11-19

Product Overview

Device connector, rear mounting
M23, Conect. plug. to be apar. poster wall, RC, straight, Screw lock, No. of poles: 12, Direction of rotation: Standard, contact type: Male, Crimped connection, Flat joint, 4xM3, Min. wall thickness: 2.7 mm, Max. wall thickness: 3.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240838
M23, Device connector on the back side, series: RC, straight, Screw lock, Number of poles: 12, Direction of rotation: standard, contact type: Male, Crimp connection, Flat seal, 4xM3, Min. wall thickness: 2.7 mm, Max. wall thickness: 3.5 mm, Coding: N, Replacement product according to RoHS II without exception 6c (Pb < 0.1 %) Reference: 1240838

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1597488
Packing unit 1
GTIN 4046356216326
Custom tariff number 85366990
Data of the insulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Contact connection method Crimp connection

Type of contacts Pin
Application Signal
Number of positions 12
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Nominal voltage, power contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Metal
Type of locking Screw locking
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC 13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-12P1N8A4100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.