INDUSTRIAL COMPONENT DATA

RC-12P1N8AB1EN 1597575 PHOENIX CONTACT Front panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-12P1N8AB1EN



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-12P1N8AB1EN
Catalog number	1597575
Category	Modular connector
Minimum order	1 Pcs
Document ID	EO-D336796868
Generated	2026-11-19

Product Overview

Front panel feed-through
M23, Front wall pass-through, RC, straight, shielded: yes, Screw lock, No. of poles: 12, Direction of rotation: Standard, type of contact: Male, Crimped connection, Flat joint, 4x Ø 3.2, Min. wall thickness: 3 mm, Max. wall thickness: 7 mm, cable diameter range: 3 mm ... 10.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240855
M23, Front panel feed-through, series: RC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Flat gasket, 4x Ø 3.2, Panel thickness min.: 3 mm, Panel thickness max.: 7 mm, cable diameter range: 3 mm ... 10.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately
Product propertiesProduct type Circular connector (cable-side)
Material specificationsHousing material Metal
ConnectorInsulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Connection method Crimp connection

Contact switching type Pin
Application Signal
Number of positions 12
Direction of rotation Standard
Connection profile 12
Contact diameterPower contacts 1 mm
Rated currentPower contacts 8 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Order information: Order contact inserts and cable clamping/shield accessories separately
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Seal
External cable diameter 3 mm ... 10.5 mm
Seal material NBR
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) 15 °C ... 25 °C
Permissible humidity (storage/transport) 50 % ... 65 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-12P1N8AB1EN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.