INDUSTRIAL COMPONENT DATA

RC-17S1N8A80KM 1602165 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-17S1N8A80KM



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-17S1N8A80KM
Catalog number	1602165
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-2BB7CA970F
Generated	2026-11-18

Product Overview

Cable connector
M23, Plug connector. for cables, straight, shielded: no, Screw lock, No. of poles: 17, Direction of rotation: Standard, contact type: Female, Crimped connection, Cable diameter range: 9.5 mm ... 10.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1241502
M23, Cable connector, straight, shielded: no, Screw locking mechanism, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 9.5 mm ... 10.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately
Product propertiesProduct type Circular connector (cable-side)
ConnectorInsulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Connection method Crimp connection
Contact switching type Socket
Application Signal
Number of positions 17

Direction of rotation Standard
Connection profile 17
Contact diameterPower contacts 1 mm
Rated currentPower contacts 8 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Order information: Order contact inserts separately
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP65
IP67
IP68
Thread type M23
Seal
External cable diameter 9.5 mm ... 10.5 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) 15 °C ... 25 °C
Permissible humidity (storage/transport) 50 % ... 65 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-17S1N8A80KM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.