INDUSTRIAL COMPONENT DATA

REL-FO/LRC-120AC/2X21/MS 1308316 PHOENIX CONTACT Plug-in miniature relay with mechanical switching position ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-FO/LRC-120AC/2X21/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-FO/LRC-120AC/2X21/MS
Catalog number	1308316
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-67C0F446F8
Generated	2026-11-19

Product Overview

Plug-in miniature relay with mechanical switching position indicator, FASTON connection, 2 switched contacts, status indication: LED (yellow), RC module, Input voltage: 120 V AC
Plug-in miniature relay with mechanical switching position indicator, FASTON connection, 2 changeover contacts, status display: Yellow LED, RC element, Input voltage: 120 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Technical dataNotesGeneral Do not use to separate SELV/PELV circuits from other circuits, because safe isolation is not guaranteed. (applies to the optocoupler variants)
General The outputs are not suitable for switching different outer conductors.
General The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.
Product propertiesProduct type Single relay
Product family ESSENTIAL edition
Operating mode 100% operating factor
Mechanical service life approx. 3x 107cycles
Relay type Electromechanical relay
Insulation characteristics: Air clearances and creepage distances between the power circuits
Insulation Basic insulation

Overvoltage category II
Pollution degree 3
Electrical propertiesMaximum power dissipation for nominal condition 1 W
Test voltage (Winding/contact) 5 kVrms(50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact) 3 kVrms(50 Hz, 1 min., changeover contact/changeover contact)
Test voltage () 1 kVrms(50 Hz, 1 min., open contact)
Air clearances and creepage distances between the power circuits
Rated insulation voltage 250 V AC
Rated surge voltage 2.5 kV
Input dataCoil side
Nominal input voltage UN 120 V AC
Input voltage range 96 V AC ... 132 V AC
Mains frequency 50/60 Hz
Drive and function monostable
Drive (polarity) non-polarized
Typical input current at UN 10 mA (50 Hz)
Input power dissipation for UN 1.2 W
Typical....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-FO/LRC-120AC/2X21/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.