INDUSTRIAL COMPONENT DATA

REL-MR-110DC/21-21/MS 1012698 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-MR-110DC/21-21/MS



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-MR-110DC/21-21/MS
Catalog number	1012698
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-6D397FAC49
Generated	2026-11-18

Product Overview

Single relay
Plug-in miniature relay, with power contact, 2 switched contacts, check button, mechanical display of switching position, status LED, free-flowing diode, polarity A1+, A2, input voltage 110 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 1012698
Packing unit 10 pc
Note Made to Order (non-returnable)
GTIN 4055626490175
Weight per Piece (excluding packing) 16.600 g
Custom tariff number 85364900
Country of origin DE (Germany)
Dimensions
Width 12.7 mm
Height 29 mm
Depth 25 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 110 V DC
Input voltage range in reference to UN see diagram
Typical input current at UN 3.6 mA
Typical response time 9 ms
Typical release time 6 ms
Contact side
Contact type 2 PDT
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 12 V (at 10 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 16 A (20 ms)
Limiting continuous current 8 A
Interrupting rating (ohmic load) max. 2000 VA (for 250 V AC)
Switching capacity according to IEC 60947-5-1 1 A (at 24 V, DC13)
1.5 A (at 24 V, AC15)
1.5 A (at 120 V, AC15)
1.5 A (at 240 V, AC15)
Motor load according to UL 508 1/4 HP, 120 V AC (N/O contact)
1/2 HP, 240 V AC (N/O contact)
General
Test voltage relay winding/relay contact 5 kV AC (50 Hz, 1 min.)
Test voltage relay contact/relay contact 5 kV AC (50 Hz, 1 min.)
Test voltage PDT/PDT 5 kV AC
Mechanical service life 5x 106cycles
Standards and Regulations
Standards/regulations EN 61810-1
VDE 0435-201
EN 50178
Environmental Product Compliance
China RoHS Environmentally Friendly Us...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-MR-110DC/21-21/MS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.