INDUSTRIAL COMPONENT DATA

REL-MR-24DC/21HC/EX 2908822 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-MR-24DC/21HC/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-MR-24DC/21HC/EX
Catalog number	2908822
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-FB239D4969
Generated	2026-11-19

Product Overview

Single relay
Plug-in miniature power relay, RT III sealed with power contacts, 1 switched contact, input voltage: 24 V DC, in combination with the corresponding PLC socket approved according to ATEX/IECEx (zone 2) and Ex zone class I, div. 2.
Pluggable miniature power relay, RT III sealed with power contacts, 1 changeover, input voltage: 24 V DC, in conjunction with the associated PLC socket approved according to ATEX/IECEx (Zone 2) and Ex-Zone Class I, Div. 2.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2908822
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4055626345161
Weight per Piece (excluding packing) 15.900 g
Custom tariff number 85364190
Country of origin AT (Austria)
Dimensions
Width 12.7 mm
Height 29 mm

Depth 15.7 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 24 V DC
Typical input current at UN 17 mA
Typical response time 7 ms
Typical release time 3 ms
Coil resistance 1440 ? ±10 % (at 20 °C)
Power dissipation for nominal condition 0.41 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 12 V (at 10 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 50 A (20 ms)
Limiting continuous current 16 A
Interrupting rating (ohmic load) max. 384 W (at 24 V DC)
58 W (at 48 V DC)
48 W (at 60 V DC)
50 W (at 110 V DC)
80 W (at 220 V DC)
4000 VA (for 250 V AC)
Switching capacity 2 A (at 24 V, DC13)
0.2 A (at 110 V, DC13)
0.2 A (at 250 V, DC13)
6 A (at 24 V, AC15)
6 A (at 120 V, AC15)
6 A (at 250 V, AC15)
General
Test voltage relay winding/relay contact 5 kV AC (50 Hz, 1 min.)
Operating mode 100% operating factor
Degree of protection RT III (wash-proof)
Mechanical service life 3x 107cycles
Service life, electrical see diagram
Mounting position any
Assembly instructions Can be aligned without spacing (> 70 °C >= 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-MR-24DC/21HC/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.