INDUSTRIAL COMPONENT DATA

# REL-OR3/LDP-125DC/3X21 2909207 PHOENIX CONTACT Plug-in octal relays with power contacts, 3 changeover contac..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-OR3/LDP-125DC/3X21**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | REL-OR3/LDP-125DC/3X21 |
| Catalog number | 2909207 |
| Category | Switching relay |
| Minimum order | 50 Pcs |
| Document ID | EO-5C2059FA3E |
| Generated | 2026-11-19 |

## Product Overview

Plug-in octal relays with power contacts, 3 changeover contacts, test button, freewheeling diode, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC
Plug-in octal relays with power contacts, 3 switches, test key, free-flowing diode, mechanical switching position indication, polarity A1+, A2-, input voltage: 125 V DC

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Relays |

## Additional Product Information

Key Commercial Data
Orderkey 2909207
Packing unit 1 pc
Minimum order quantity 50 pc
Catalog page Page 308 (C-5-2019)
GTIN 4055626360171
Weight per Piece (excluding packing) 88.000 g
Custom tariff number 85364900
Country of origin PL (Poland)
Drawings

Dimensions
Coil side
General
Standards and Regulations
Classifications
Note
Ambient conditions
Contact side
Connection data
Environmental Product Compliance
Drawings
Diagram
Operating voltage range
Diagram
Interrupting rating
Diagram
Electrical service life
Diagram
Service life reduction factor
Circuit diagram
Back to topNote
Note The outputs are not suitable for switching different outer conductors.
Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.
Back to topDimensions
Width 35 mm
Height 35 mm
Depth 54.4 mm
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Maximum altitude <= 2000 m
Degree of protection RT I
>= IP54 (Installation location)
Back to topCoil side
Nominal input voltage UN 125 V DC
Typical input current at UN 14 mA
Typical response time 18 ms
Typical release time 20 ms
Protective circuit Damping diode
Status display Yellow LED
Voltage type for actuation DC
Power dissipation for nominal condition 1.44 W
Back to topContact side
Contact type 3 PDTs
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V DC

440 V AC

Minimum switching voltage 10....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-OR3/LDP-125DC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.