INDUSTRIAL COMPONENT DATA

REL-OR3/LDP-220DC/3X21 2907027 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-OR3/LDP-220DC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-OR3/LDP-220DC/3X21
Catalog number	2907027
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-3E49468FA7
Generated	2026-11-19

Product Overview

Single relay
Plug-in octal relay with power contacts, 3 inverters, test button, indication of the mechanical switching position, coil voltage: 220VDC, actuation voltage at 23°C without pre-excitation >=60% ... ?80% of the assigned voltage (>=132VDC... <=176VDC)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2907027
Packing unit 10 pc
Catalog page Page 322 (C-5-2017)
GTIN 4055626159959
Weight per Piece (excluding packing) 92.000 g
Custom tariff number 85364900
Country of origin PL (Poland)
Dimensions
Width 35 mm
Height 35 mm
Depth 54.4 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 220 V DC
Input voltage range in reference to UN see diagram
Typical input current at UN 8 mA
Typical response time 18 ms
Typical release time 7 ms
Protective circuit Damping diode
Status display Yellow LED
Power dissipation for nominal condition 1.76 W
Contact side
Contact type 3 PDTs
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 10 V (At 24 mA)
Min. switching current 10 mA (at 24 V)
Maximum inrush current 30 A (20 ms, N/O contact)
Limiting continuous current 10 A
Interrupting rating (ohmic load) max. 240 W (at 24 V DC)
124 W (at 48 V DC)
108 W (at 60 V DC)
52 W (at 110 V DC)
48 W (at 220 V DC)
2500 VA (for 250 V AC)
Switching capacity min. 0.24 W
Switching capacity 2 A (at 24 V, DC13)
1.5 A (at 230 V, AC15)
General
Test voltage relay winding/relay contact 2.5 kVrms(50 Hz, 1 min.)
Test voltage PDT/PDT 2 kVrms(50 Hz, 1 min.)
Operating mode 100% operating factor
Degree of protection RT I
Mechanical service life 1x 107cycles, approximately
Mounting position any
Net weight (SAP) 92 g
St...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-OR3/LDP-220DC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.