INDUSTRIAL COMPONENT DATA

REL-PR1-220DC/1/MB 2908046 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-PR1-220DC/1/MB



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-PR1-220DC/1/MB
Catalog number	2908046
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-A198C29739
Generated	2026-11-18

Product Overview

Single relay
Pluggable high-power relay with power contacts, special for connecting high DC loads, 1 normally open contact, shut-off magnet, coil voltage: 220 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2908046
Packing unit 1 pc
Catalog page Page 328 (C-5-2017)
GTIN 4055626266909
Weight per Piece (excluding packing) 82.700 g
Custom tariff number 85364900
Country of origin PL (Poland)
Dimensions
Width 38.6 mm
Height 36.1 mm
Depth 45.5 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 220 V DC
Input voltage range in reference to UN see diagram
Typical input current at UN 7.3 mA
Typical response time 20 ms
Typical release time 15 ms
Power dissipation for nominal condition 1.61 W
Contact side
Contact type 1 N/O contact
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 440 V AC
250 V DC
Minimum switching voltage 5 V (At 24 mA)
Min. switching current 5 mA (at 24 V)
Maximum inrush current 50 A (20 ms)
30 A (4 s)
Limiting continuous current 16 A
Interrupting rating (ohmic load) max. 384 W (at 24 V DC)
768 W (at 48 V DC)
930 W (at 60 V DC)
1650 W (at 110 V DC)
2640 W (at 220 V DC)
4000 VA (for 250 V AC)
Switching capacity min. 120 mW
Switching capacity 1 A (at 220 V, DC13)
1.5 A (at 240 V, AC15)
General
Test voltage relay winding/relay contact 2.5 kV
Operating mode 100% operating factor
Degree of protection RT I
Mechanical service life approx. 2x 107cycles
Service life, electrical see diagram
Mounting position any
Net weight (SAP) 82.7 g
Standards and Regulations
Standards/regulations IEC 60664
IEC 61810
Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-PR1-220DC/1/MB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.