INDUSTRIAL COMPONENT DATA

REL-PR3-48DC/3X21 2908894 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-PR3-48DC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-PR3-48DC/3X21
Catalog number	2908894
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-F117B62EA6
Generated	2026-11-19

Product Overview

Single relay
Pluggable high-power relays with power contacts, 3 open contacts, coil voltage: 48VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2908894
Packing unit 1 pc
GTIN 4055626353920
Weight per Piece (excluding packing) 85.100 g
Custom tariff number 85364190
Country of origin PL (Poland)
Dimensions
Width 38.6 mm
Height 36.1 mm
Depth 45.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side
Nominal input voltage UN 48 V
Typical input current at UN 28 mA
Typical response time 20 ms
Typical release time 15 ms
Coil resistance 1750 ? ±10 %
Contact side
Contact type 3 PDTs
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 440 V AC
250 V DC
Minimum switching voltage 10 V (At 24 mA)
Min. switching current 10 mA (at 24 V)
Maximum inrush current 50 A (20 ms, N/O contact)
Limiting continuous current 16 A
Interrupting rating (ohmic load) max. 384 W (at 24 V DC)
124 W (at 48 V DC)
108 W (at 60 V DC)
52 W (at 110 V DC)
70 W (at 220 V DC)
4000 VA (for 250 V AC)
4000 VA (at 440 V AC)
3-phase motor load 1500 W (at 400 V, AC3)
Motor load according to UL 508 1/3 HP, 120 V AC (single-phase AC motor)
1/2 HP, 240 V AC (single-phase AC motor)
1/2 HP, 240 V AC (three-phase induction motor)
General
Note The outputs are not suitable for switching different outer conductors.
Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.
Test voltage relay winding/relay contact 2.5 kVrms(50 Hz, 1 min.)
Test voltage PDT/PDT 2.5 kVrms(50 Hz, 1 min.)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-PR3-48DC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.