INDUSTRIAL COMPONENT DATA

EMG 17-REL/KSR-W230/21-21-LCAU 2941468 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 17-REL/KSR-W230/21-21-LCAU



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 17-REL/KSR-W230/21-21-LCAU
Catalog number	2941468
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-13C5E8E06E
Generated	2026-11-18

Product Overview

Relay Module
Relay module, with soldered mini-switching relay, contact (AgNi+Au): small to large powers, 2 switched contacts, input voltage 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2941468
Packing unit 10 pc
Catalog page Page 135 (IF-2011)
GTIN 4017918080464
Weight per Piece (excluding packing) 56.370 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 17.5 mm
Height 75 mm

Depth 62.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 40 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 230 V AC
Input voltage range in reference to UN 0.85 ... 1.1
Mains frequency 50/60 Hz
Typical input current at UN 4 mA
Typical response time 7 ms
3 ms ... 12 ms
Typical release time 3 ms
Typical release time range 2 ms ... 9 ms
Operating voltage display Glow lamp
Power dissipation for nominal condition 0.92 W
Contact side
Contact type Single contact, 2-PDT
Type of switch contact Single contact
Contact material AgNi, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Maximum inrush current 0.2 A
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Contact side (with destroyed gold layer)
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 250 V AC/DC
Limiting continuous current 5 A
Maximum inrush current 6 A
Interrupting rating (ohmic load) max. 120 W (at 24 V DC)
95 W (at 48 V DC)
60 W (at 60 V DC)
40 W (at 110 V DC)
55 W (at 220 V DC)
1250 VA (for 250 V AC)
General
N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 17-REL/KSR-W230/21-21-LCAU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.