
INDUSTRIAL COMPONENT DATA

FLT-SEC-H-T1-264/25-P 2905968 PHOENIX CONTACT Type 1 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLT-SEC-H-T1-264/25-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLT-SEC-H-T1-264/25-P
Catalog number	2905968
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-BBB8783D62
Generated	2026-11-19

Product Overview

Type 1 surge protection plug
Replacement connector for lightning current arresters from the FLASHTRAB SEC HYBRID 264 product series, for the L-N and L-PEN sections.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2905968
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 28 (C-4-2017)
GTIN 4055626012032
Weight per Piece (excluding packing) 335.780 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 113.4 mm
Width 35.5 mm
Depth 64.2 mm

Horizontal pitch 2 Div.
Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 4000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
General
IEC test classification I / II
T1 / T2
EN type T1 / T2
IEC power supply system TN-C
Mode of protection L-PEN
Mounting type on base element
Color light grey RAL 7035
Housing material PA 6.6-FR 20% GF
PBT-FR
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type Male
Number of positions 1
Surge protection fault message optical
Protective circuit
Nominal voltage UN 240 V AC (TN)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 264 V AC
Nominal discharge current In(8/20) µs 25 kA
Maximum discharge current Imax(8/20) µs 50 kA
Impulse discharge current (10/350) µs, charge 12.5 As
Impulse discharge current (10/350) µs, specific energy 160 kJ/?
Impulse discharge current (10/350) µs, peak value limp 25 kA
Follow current interrupt rating Ifi 50 kA
Short-circuit current rating ISCCR 50 kA
Voltage protection level Up <= 1.5 kV
Residual voltage Ures <= 1.5 kV (at In)
<= 2.5 kV (at 50 kA)
<=...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLT-SEC-H-T1-264/25-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.