INDUSTRIAL COMPONENT DATA

FLT-SEC-P-T1-440/35-P 2905989 PHOENIX CONTACT Type 1 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLT-SEC-P-T1-440/35-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLT-SEC-P-T1-440/35-P
Catalog number	2905989
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-9DD139827F
Generated	2026-11-18

Product Overview

Type 1 surge protection plug
Replacement connector for lightning current arresters from the FLASHTRAB SEC PLUS 440 product series, for the L-N and L-PE sections.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2905989
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 29 (C-4-2017)
GTIN 4055626013282
Weight per Piece (excluding packing) 241.750 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 46.6 mm
Width 35.5 mm
Depth 59.4 mm

Horizontal pitch 2 Div.
Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (5 - 500 Hz/2.5 h/X, Y, Z)
General
IEC test classification I / II
T1 / T2
EN type T1 / T2
IEC power supply system TT
Mode of protection L-N
L-PE
L-PEN
N-PE (4+0)
Mounting type on base element
Color light grey RAL 7035
Housing material PA 6.6-FR 20% GF
PBT-FR
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type Male
Number of positions 1
Surge protection fault message optical
Protective circuit
Nominal voltage UN 400 V AC (TN)
400 V AC (IT)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 440 V AC
Residual current IPE < 5 µA
Nominal discharge current In(8/20) µs 35 kA
Maximum discharge current Imax(8/20) µs 50 kA
Impulse discharge current (10/350) µs, charge 17.5 As
Impulse discharge current (10/350) µs, specific energy 310 kJ/?
Impulse discharge current (10/350) µs, peak value limp 35 kA
Follow curr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLT-SEC-P-T1-440/35-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.