INDUSTRIAL COMPONENT DATA

RF-17P1N8AW400 1607857 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-17P1N8AW400



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-17P1N8AW400
Catalog number	1607857
Category	Circular connector, mounting (without cable)
Minimum order	20 Pcs
Document ID	EO-5CEBE04114
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, straight, Screw lock, M23, number of poles: 17, contact type: Male, Axial O-ring, 4x Ø2.7, shielded: yes, protection index: IP67, number of poles: 17, connection type: Crimped connection, series: RF
Device connector front mounting, straight, Screw locking mechanism, M23, number of positions: 17, contact connection type: Pin, Axial O-ring, 4x Ø 2.7 mm, shielded: yes, number of positions: 17, connection method: Crimp connection, series: RF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesOrder information: Order crimp contacts Ø 1 mm separately
MountingMounting type Front mounting
Mounting 4x Ø 2.7 mm
Product propertiesProduct type Circular connectors (device side)
Series RF
Application Signal
Signal
Number of positions 17
Connection profile 17
Shielded yes

Coding N
Thread type M23
Data management status
Article revision 03
Material specificationsSeal material FPM
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Electrical propertiesContact
Contact diameter 1 mm
Max. current 8 A
Nominal voltage UN 48 V AC 74 V DC
Overvoltage category III
Degree of pollution 3
Rated surge voltage 1.5 kV
Connection dataConductor connection
Connection method Crimp connection
Contact connection type Pin
ConnectorType straight
Direction of rotation Standard
Environmental and real-life conditionsAmbient conditions
Degree of protection IP67
Ambient temperature (operation) -40 °C ... 125 °C
Altitude 2000 m

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-17P1N8AW400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.