INDUSTRIAL COMPONENT DATA

RIF-2-BSC/4X21/EX 1047031 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: RIF-2-BSC/4X21/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	RIF-2-BSC/4X21/EX
Catalog number	1047031
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-E4DF02C988
Generated	2026-11-18

Product Overview

Relay base
RIF-2.../EX relay socket for equipping with sealed RTIII industrial relays with 4 switched contacts for use in zone 2, screw connection, socket for input/anti-parasitic modules, for rail mounting NS 35/7.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 1047031
Packing unit 10 pc
GTIN 4055626646114
Weight per Piece (excluding packing) 68.000 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Width 27 mm
Height 89 mm
Depth with retaining bracket 75 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C (Related to the assembly)
Ambient temperature (storage/transport) -40 °C ... 85 °C

Input data
Protective circuit depending on the selected input/suppressor modules
Connection data, input side
Connection name Input side
Connection method Screw connection
Stripping length 8 mm
Conductor cross section solid 0.5 mm² ... 4 mm²
Conductor cross section flexible 0.5 mm² ... 4 mm²
0.5 mm² ... 4 mm² (Ferrule with plastic sleeve)
Conductor cross section flexible (2 conductors with same cross section) 0.5 mm² ... 2.5 mm²
0.5 mm² ... 1.5 mm² (TWIN ferrule with plastic sleeve)
Conductor cross section AWG 20 ... 10 (solid)
20 ... 12 (flexible)
Torque 0.5 Nm ... 0.6 Nm
Connection data, output side
Connection name Contact side
Connection method Screw connection
Stripping length 8 mm
Conductor cross section solid 0.5 mm² ... 4 mm²
Conductor cross section flexible 0.5 mm² ... 4 mm²
0.5 mm² ... 4 mm² (Ferrule with plastic sleeve)
Conductor cross section flexible (2 conductors with same cross section) 0.5 mm² ... 2.5 mm²
0.5 mm² ... 1.5 mm² (TWIN ferrule with plastic sleeve)
Conductor cross section AWG 20 ... 10 (solid)
20 ... 12 (flexible)
Torque 0.5 Nm ... 0.6 Nm
General
Nominal v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RIF-2-BSC/4X21/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.