INDUSTRIAL COMPONENT DATA

C-RC 120/M10 DIN 3240125 PHOENIX CONTACT Ring cable lug

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-RC 120/M10 DIN



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-RC 120/M10 DIN
Catalog number	3240125
Category	Solderless copper terminals for copper conductors
Minimum order	25 Pcs
Document ID	EO-FDB2C4D11A
Generated	2026-11-18

Product Overview

Ring cable lug
Ring cable lug, uninsulated, 120 mm², M10

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox

Additional Product Information

Technical dataProduct propertiesProduct type Connector
Data management status
Article revision 00
DimensionsDimensional drawing
Width 24 mm
Sleeve length 56 mm
Length of the insulating material sleeve 22 mm
Maximum stripping length 25 mm
Distance from the center to the insulating material sleeve 22 mm
Min. material thickness 3 mm
Inner dimensions of the insulating collar 16.5 mm
Internal dimensions
Internal diameter 10.5 mm
Material specificationsColor silver-colored

Material Copper
Coating tin-plated
Mechanical propertiesTechnical data
Sleeve length 56 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) 110 °C
Standards and regulationsDesign according to standard DIN 46234

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-RC 120/M10 DIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.