INDUSTRIAL COMPONENT DATA

C-RC 16/M12 DIN 3240098 PHOENIX CONTACT Ring cable lug

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-RC 16/M12 DIN



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-RC 16/M12 DIN
Catalog number	3240098
Category	Solderless copper terminals for copper conductors
Minimum order	100 Pcs
Document ID	EO-EF7C96463B
Generated	2026-11-18

Product Overview

Ring cable lug
Ring cable lug, uninsulated, 16 mm², M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox

Additional Product Information

Technical dataProduct propertiesProduct type Connector
Data management status
Article revision 00
DimensionsDimensional drawing
Width 22 mm
Sleeve length 37 mm
Length of the insulating material sleeve 10 mm
Maximum stripping length 13 mm
Distance from the center to the insulating material sleeve 16 mm
Min. material thickness 1.2 mm
Inner dimensions of the insulating collar 5.8 mm
Internal dimensions
Internal diameter 13 mm
Material specificationsColor silver-colored
Material Copper

Coating tin-plated
Mechanical propertiesTechnical data
Sleeve length 37 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) 110 °C
Standards and regulationsDesign according to standard DIN 46234

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-RC 16/M12 DIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.