INDUSTRIAL COMPONENT DATA

# C-RCI 6/M8 3240030 PHOENIX CONTACT Terminal de cable anular

**Brand: PHOENIX CONTACT | Manufacturer Part Number: C-RCI 6/M8**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | C-RCI 6/M8 |
| Catalog number | 3240030 |
| Category | Solderless copper terminals for copper conductors |
| Minimum order | 25 Pcs |
| Document ID | EO-845127A653 |
| Generated | 2026-11-18 |

## Product Overview

Terminal de cable anular
Ring wire terminal, yellow, 4 ... 6 mm², M8
Ring cable lug, yellow, 4 ... 6 mm2, M8

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > TOOL fox |

## Additional Product Information

Technical dataProduct propertiesProduct type Connector
Data management status
Article revision 00
Electrical propertiesFuse yes
DimensionsDimensional drawing
Width 15 mm
Sleeve length 34.9 mm
Length of the insulating material sleeve 14 mm
Maximum stripping length 9 mm
Distance from the center to the insulating material sleeve 13.4 mm
Min. material thickness 1 mm
Inner dimensions of the insulating collar 6.6 mm
Internal dimensions

Internal diameter 8.5 mm
Material specificationsColor yellow (RAL 1018)
Material Copper
Flammability rating according to UL 94 V2
Coating tin-plated
Insulating material PA
Components halogen-free
Mechanical propertiesTechnical data
Sleeve length 34.9 mm
Environmental and real-life conditionsAmbient conditions
Optimum ambient temperature (storage/transport) 20.00 °C 50.00 % Humidity (RH), store inside sealed original packaging.
Avoid direct sunlight and heat.
Ambient temperature (operation) -20 °C ... 105 °C
Ambient temperature (assembly) -20 °C ... 100 °C
Short-term temperature 100 °C
Standards and regulationsDesign according to standard JIS, UL, CSA

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-RCI 6/M8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.