INDUSTRIAL COMPONENT DATA

VS-08-BU-RJ45-6/KA/LSA 1653168 PHOENIX CONTACT RJ45 socket insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-08-BU-RJ45-6/KA/LSA



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-08-BU-RJ45-6/KA/LSA
Catalog number	1653168
Category	Fibre optic attenuator
Minimum order	5 Pcs
Document ID	EO-5A614BAD29
Generated	2026-11-18

Product Overview

RJ45 socket insert
RJ45 Female Insert, Modular (Keystone), CAT6, 8 Pole, Shielded, Wired (LSA), for Wire and Rigid Conductors AWG 26 ... 22

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1653168
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 337 (C-4-2015)
GTIN 4017918970086
Weight per Piece (excluding packing) 15.820 g
Custom tariff number 85366990
Country of origin CN (China)
Mechanical characteristics
Number of positions 8
Number of slots 1
Shielded yes

Insertion/withdrawal cycles >= 1000
Connection method LSA
Conductor cross section 0.13 mm² ... 0.25 mm² (solid)
0.14 mm² ... 0.25 mm² (flexible)
Connection cross section AWG 26 ... 23 (solid)
26 ... 23 (flexible)
Max. cable diameter 10 mm
Mounting type Latching hook mounting
Degree of protection IP20
Ambient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Material data
Flammability rating according to UL 94 V0
Housing material PC+ABS
Contact material Phosphor bronze
Contact surface material Gold
Electrical characteristics
Number of positions 8
Nominal current IN 2 A
GRP transmission properties CAT6
Transmission speed 1 Gbps
Rated current 2 A
Overvoltage category II
Degree of pollution 2
Rated voltage (III/3) 72 V (DC)
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027440205eCl@ss 9.027440205
ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC000438...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-08-BU-RJ45-6/KA/LSA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.