INDUSTRIAL COMPONENT DATA

FLK 26/EZ-DR/1000/KONFEK 2299466 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLK 26/EZ-DR/1000/KONFEK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLK 26/EZ-DR/1000/KONFEK
Catalog number	2299466
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-3AEC31BBB8
Generated	2026-11-18

Product Overview

Cable
Ready-made round cable; Connection 1: IDC/FLK Connection Female (1x 26-poles); Connection 2: IDC/FLK Connection Female (1x 26-poles); Cable length: 10 m
Pre-assembled round cable; Connector 1: IDC/FLK socket header (1x 26-pin); Connector 2: IDC/FLK socket header (1x 26-pin); Cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2299466
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 589 (C-5-2017)
GTIN 4017918886189
Weight per Piece (excluding packing) 936.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
General
Nominal voltage UN < 50 V AC

60 V DC
Max. current carrying capacity per path 1 A
Max. conductor resistance 0.16 ?/m
Length of cable 10 m
Single wire, cross section 0.14 mm²
Single wire, cross section [AWG] 26
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
External diameter 7.8 mm
Cable, preassembly Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding no
Outer sheath, material PVC
External sheath, color gray RAL 7035
Environmental conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Flame resistance IEC 60332-1
DIN VDE 0482 Part 332-1
Resistance to oil DIN VDE 0472 Part 803, test type B
Gasoline resistance against occasional splashes
Connector 1
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 26
Pitch 2.54 mm
Connector 2
Connection name Controller level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 26
Pitch 2.54 mm
Supported controller
Controller universal
Color code
Connector 1 = connector 2 (optional) = wire color IDC/FLK26 (1) = IDC/FLK26 (1) = black
IDC/FLK26 (2) = IDC/FLK26 (2) = brown
IDC/FLK26 (3) = IDC/FLK26...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLK 26/EZ-DR/1000/KONFEK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.