INDUSTRIAL COMPONENT DATA

RPI-BC 107,6 EXT DEV-KIT KMGY 1107460 PHOENIX CONTACT DIN rail housing for Raspberry Pi computers (suitable ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RPI-BC 107,6 EXT DEV-KIT KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	RPI-BC 107,6 EXT DEV-KIT KMGY
Catalog number	1107460
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-7BCC37A625
Generated	2026-11-18

Product Overview

DIN rail housing for Raspberry Pi computers (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of lower part, upper part, cover, perfboard, and holder for connecting the HBUS and GPIO strip; housing in accordance with DIN 43880 DIN rail housing for Raspberry Pi computer (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of the bottom, top, cover, perforated frame plates and brackets for the connection of the HBUS and GPIO strip; Housing according to DIN43880

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1107460
Packing unit 1
GTIN 4063151008789
Custom tariff number 85366990
Drawings
Dimensions
Ambient conditions
Packaging information

Classifications
Item properties
Material data
PCB data
Standards and regulations
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Electronic housing
Type RPI-BC 107,6 EXT DEV-KIT KMGY
Order No. 1107460
Housing type DIN rail housing
Type Housing set
Max. IP code to attain IP20
Mounting type Snap in
Back to topDimensions
Dimensional drawing
Width [w] 107.6 mm
Height [h] 89.7 mm
Depth [d] 62.2 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Back to topPCB data
Form factor Raspberry Pi
Back to topPackaging information
Pieces per package 1
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RPI-BC 107,6 EXT DEV-KIT KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.