INDUSTRIAL COMPONENT DATA

# SAC-14P- 5,0-PUR/M16FRX 1260742 PHOENIX CONTACT Main cable, application: Sensor/actuator box, number of plug..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-14P-5,0-PUR/M16FRX**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SAC-14P-5,0-PUR/M16FRX |
| Catalog number | 1260742 |
| Category | Sensor-actuator patch cord |
| Minimum order | 1 Pcs |
| Document ID | EO-7BFD18378F |
| Generated | 2026-11-18 |

## Product Overview

Main cable, application: Sensor/actuator box, number of plug-in stations: 10, number of poles: 14, occupancy of plug-in stations: single, status indication: no; main cable connection: M16 plug-in connection, PUR/PVC, cable length: 5 m, shielding: no, The item does not contain lead according to the RoHS II directive without the exception 6c (Pb< 0.1%)
Main cable
Master cable, application: Sensor/actuator box, connection method: M8 socket, number of slots: 10, number of positions: 14, slot assignment: single, status display: No; master cable connection: M16 plug connection, PUR/PVC, cable length: 5 m, shielding: no, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Technical dataProduct propertiesProduct type Master cable, assembled
Number of positions 14
Application Sensor/actuator box
Number of slots 10
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Connection dataConnection method Fixed connection
Cross section AWG (converted acc. to IEC)
SignalingStatus display present No

Material specificationsMaterial PUR
Cu alloy
Seal material NBR
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of contact, master cable side CU alloy
Material of the contact carrier on the master cable side TPU
Material of contact surface, master cable side gold-plated
Cable/lineCable length 5 m
PUR/PVC black [PUR]
Dimensional drawing
Cable weight 111.1 kg/km
UL AWM Style 20549
Number of positions 12
Shielded no
Cable type PUR/PVC black [PUR]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section 10x 0.34 mm² (Signal line)
2x 0.75 mm² (power line)
Wire diameter incl. insulation 1.3 mm ±0.1 mm (Signal line)
1.8 mm ±0.1 mm (power line)
External cable diameter 8.6 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, white, green, yellow, gray, pink, red, black, violet, white/pink, pink/brown
Inner sheath thickness >= 0.15 mm
Thickness, outer sheath >= 0.38 mm
Overall twist Wires twisted in layers
Nominal voltage, cable 300 V
Test voltage 2000 V
Minimum bending rad...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-14P-5,0-PUR/M16FRX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.