INDUSTRIAL COMPONENT DATA

SAC-2P-DTMS/0,3PUR/M12FS4P SKF 1426044 PHOENIX CONTACT Cable for sensors/actuators SAC-2P-DTMS/0,3 PUR/M12FS..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-DTMS/0,3PUR/M12FS4P SKF

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-DTMS/0,3PUR/M12FS4P SKF
Catalog number	1426044
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-3A99BB610D
Generated	2026-11-19

Product Overview

Cable for sensors/actuators - SAC-2P-DTMS/0,3 PUR/M12FS4P SKF - 1426044
Sensor/actuator cable, 2-pole, halogen-free PUR, grayish black RAL 7021, Straight male connector DEUTSCH DT04-2P Clip lock, to Straight connection female M12, coding: A, cable length: 0.3 m, Special connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators, 2-pole, PUR halogen-free, black-gray RAL 7021, Plug straight male DEUTSCH DT04-2P Lock-clip, a connection socket straight M12, coded, cable length: 0.3 m, special Connection
Data commercial
Key order One million four hundred twenty six thousand forty four
Packing unit 1 pcs
Key selling BF1DWA -
EAN Four trillion fifty five billion six hundred twenty six million four hundred thirty seven thousand eight hundred fifty nine
Unit weight (excluding packaging) 35,200 g
Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety
Measures
Cable length 0.3 m

Environmental conditions
Room temperature (service) -20 °C ... 80 °C (male / female)
Overview
Current sizing at 40 °C 8 To
Tension sizing 48 V AC
48 V DC
Number of poles Two
Insulation resistance >= 100 M?
Encoding A - standard
Status indication Not
Protective circuit/component protection without connect
Material
Class of flammability according to UL 94 V2
Material contact CuSn
Material contact surface Ni/Au
Material support of contacts TPU GF
Material body grip TPU fire-retardant, self-extinguishing
Material contact valve connector Cu alloy
Material contact surface valve connector nickel-plated
Material insert with contacts connector valve PA 6.6
Material housing valve connector PA
Material knurled Die-cast zinc, nickel plated
Material of the board Silicone
Standards and specifications
Flame resistance according to UL 758/1581 (horizontal)
according to UL 758/1581 FT2
a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-DTMS/0,3PUR/M12FS4P SKF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.