INDUSTRIAL COMPONENT DATA

SAC-2P-M12MSB/20-910/M12FSB PF 1110577 PHOENIX CONTACT Bus system cable, PROFIBUS (12 Mbps), 2-position, PUR..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M12MSB/20-910/M12FSB PF



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M12MSB/20-910/M12FSB PF
Catalog number	1110577
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-A29AFD2221
Generated	2026-11-19

Product Overview

Bus system cable, PROFIBUS (12 Mbps), 2-position, PUR halogen-free, violet RAL 4001, shielded, cable length: 20 m
Bus system cable, PROFIBUS (12 MBit/s), 2-pole halogen-free, shielded, M12 straight connector, encoding: B SPEEDCON, a Straight female M12, coding: A SPEEDCON, cable length: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1110577
Packing unit 1
GTIN 4063151027056
Custom tariff number 85444290
Drawings
General
Cable
Dimensions
Material
Classifications

Drawings
Dimensional drawing
Plug, M12 x 1, straight, shielded
Dimensional drawing
M12 x 1 socket, straight, shielded
Circuit diagram
Schematic diagram
Pin assignment M12 male connector, 5-pos., B-coded, male side
Schematic diagram
Pin assignment M12 socket, 5-pos., B-coded, female side
Cable cross section
PROFIBUS [910]
Back to topDimensions
Length of cable 20 m
Back to topGeneral
Note Further products with variable cable lengths can be found in the accessories section
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 2
Coding B - inverse
Signal type/category PROFIBUS, 12 Mbps (max. 100 m)
Status display No
Overvoltage category II
Degree of pollution 3
Back to topMaterial
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA 6.6 (plug), TPU GF (socket)
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Back to topCable
Cable type PROFIBUS
Cable type (abbreviation) 910
UL AWM style 21198 (80°C/300 V)
Cable structure 1x2xAWG24/19
Conductor cross section 2x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 19x 0.13 mm
Core diameter including insulation 2.55 mm ±0.07 mm
Wire colors Red, green
Overall twist 2 cores with 2 fillers to the core
Shielding Plastic-coated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M12MSB/20-910/M12FSB PF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.