INDUSTRIAL COMPONENT DATA

SAC-2P-M12MSB/ 5,0-915 1525487 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-2P-M12MSB/ 5,0-915



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-2P-M12MSB/ 5,0-915
Catalog number	1525487
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-97D6B248C5
Generated	2026-11-19

Product Overview

Bus system cable
Bus system cable, PROFIBUS, 2-pole, shielded, Straight M12 connector, encoding: B, a free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1525487
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4017918950149
Weight per Piece (excluding packing) 390.300 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67

General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 2
Insulation resistance >= 100 M?
Coding B - inverse
Signal type/category PROFIBUS
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Pin assignment
Contact | Color (signal designation) | Contact (optional) 2 (Plug) | GN (A cable)
4 (Plug) | RD (B cable)
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type PROFIBUS
Cable type (abbreviation) 915
Cable structure 1x2xAWG24/19
Conductor cross section 2x 0.25 mm²
AWG signal line 24
Conductor structure signal line 19x 0.14 mm
Core diameter including insulation 2.56 mm
Wire colors Red, green
Overall twist 2 wires, twisted
Shielding Aluminum-coated foil, tinned copper braided shield
Optical shield covering 70 %
External sheath, color blue
Outer....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-2P-M12MSB/ 5,0-915 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.