INDUSTRIAL COMPONENT DATA

SAC-3P-0,5-PUR/M12FS 0,08 1415991 PHOENIX CONTACT Sensor/actuator cable SAC-3P-0,5-PUR/M12FS 0,15 1415991

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-0,5-PUR/M12FS 0,15



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-0,5-PUR/M12FS 0,15
Catalog number	1415991
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-7B988DD4F3
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-3P-0,5-PUR/M12FS 0,15 - 1415991
Sensor/Actuator Cable, 3-Pole, Halogen-Free PUR, Grey-Black RAL 7021, Free Cable End, to Straight Connecting Female M12, Coding: A, Cable Length: 0.5 m, 150 mm Free End
Sensor/actuator cable, 3-pin, halogen-free, grey-black RAL 7021, free conductor end, on M12 straight socket, coding: A, cable length: 0.5 m, free end 150 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, A-coded, cable length: 0.5 m, 150 mm free end
Key Commercial Data
Orderkey 1415991
Packing unit 1
GTIN 4055626055299
Custom tariff number 85444290
Dimensions
Length of cable 0.5 m
Stripping length of the free conductor end 50 mm
Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549
Conductor cross section 3x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-0,5-PUR/M12FS 0,15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.