INDUSTRIAL COMPONENT DATA

SAC-3P-10,0-PUR/M12FR VC 1402554 PHOENIX CONTACT Sensor/actuator cable SAC-3P-10,0-PUR/M12FR VC 1402554

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-PUR/M12FR VC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-10,0-PUR/M12FR VC
Catalog number	1402554
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-8438F44DEE
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-3P-10,0-PUR/M12FR VC - 1402554
Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Elbow connection female M12, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, A-coded, cable length: 10 m
Key Commercial Data
Orderkey 1402554
Packing unit 1
GTIN 4046356622646
Custom tariff number 85444290
Dimensions
Length of cable 10 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67

IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.5 mm²
AWG signal line 20
Conductor structure signal line 28x 0.15 mm
Core diameter including insulation 1.5 mm ±0.05 mm (Signal line)
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter D 4.5 mm ±0.2 mm
Smallest bending radius, fixed installation 22.5 mm
Number of bending cycles 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-PUR/M12FR VC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.