INDUSTRIAL COMPONENT DATA

SAC-3P-15,0-PVC/M12FR-2L 1508417 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-15,0-PVC/M12FR-2L



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-15,0-PVC/M12FR-2L
Catalog number	1508417
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-AECE5DB250
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole, PVC, black RAL 9005, free cable end, to Elbow connection female M12, coding: A, with 2 LEDs, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1508417
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4017918895372
Weight per Piece (excluding packing) 433.000 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 15 m
Stripping length of the free conductor end 50 mm
Ambient conditions
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 24 V
24 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Status display 2 LEDs
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section 3x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 19x 0.15 mm
Core diameter including insulation 1.26 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color black RAL 9005
Outer sheath thickness >= 0.76 mm
External cable diameter D 4.3 mm ±0.2 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-15,0-PVC/M12FR-2L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.