INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MR/2,2-PUR/4PM8FS HG 1572304 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MR/2,2-PUR/4PM8FS HG

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MR/2,2-PUR/4PM8FS HG
Catalog number	1572304
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-7D8220E47B
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, Angled male connector M8, to Straight connection female M8, cable length: 2.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1572304
Packing unit 5 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356432153
Weight per Piece (excluding packing) 59.840 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 2.2 m
Ambient conditions
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
Length of twist, overall twist 40 mm
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 3.6 mm ±0.15 mm
Smallest bending radius, fixed installation 18 mm
Sm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MR/2,2-PUR/4PM8FS HG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.