INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MS/ 5,5-PUR/M 8FR 1501320 PHOENIX CONTACT Cable for sensors/actuators, 3-pole, PUR halogen-free, b..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MS/ 5,5-PUR/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MS/ 5,5-PUR/M 8FR
Catalog number	1501320
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-8A607F95C2
Generated	2026-11-19

Product Overview

Cable for sensors/actuators, 3-pole, PUR halogen-free, black-gray RAL 7021, male Connector straight M8, to Female connection angled M8, cable length: 5,5 m
Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, Straight male connector M8, to Angled connection female M8, cable length: 5.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable, sensor-actuator, 3-pin, PUR without halogenated, black-grey RAL 7021, Male straight M8, on Female angled M8, cable length: 5,5 m
Commercial data
The code for the order One million five hundred one thousand three hundred twenty
Pieces/pack. 5 PCS
Sales key BF1BBA -
The amount of minimum order 25 PCS
GTIN Four trillion seventeen billion nine hundred eighteen million six hundred thirteen thousand five hundred thirty two
Weight per piece (package included) 115,380 g
Number customs tariff Eighty five million four hundred forty four thousand two hundred ninety
Country of origin DE (Germany)
Size

Length. cable 5.5 m
Environmental conditions
Degree of protection IP65
IP67
IP68
General
Rated current at 40 °C 4 To
Rating voltage 48 V AC
60 V DC
N. of poles Three
Insulation resistance >= 100 M?
Encoding A - standard
Signalling status of No
Overvoltage category II
Pollution degree Three
Material
Class behaviour according to UL 94 HB
Contact material CuSn
Material surface contacts Ni/Au
Insert material latch TPU GF
Material handles TPU, hardly inflammable, self-extinguishing
Nut material Zinc die-cast, nickel-plated
Material gasket NBR
Regulations and requirements
Class behaviour according to UL 94 HB
Cable
Cable type EVEN without halogenated black
Cable type (abbreviation) WHILE
Abbreviation cables Li9Y11Y-HF
UL AWM Style Twenty thousand five hundred forty nine
Conductor cross section 3x 0.25 mm2
Signal line AWG Twenty four
Tree conductor signal line 32x 0.10 mm
Wire diameter inclu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MS/ 5,5-PUR/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.