INDUSTRIAL COMPONENT DATA

SAC-3PM12MS/4,0-PUR/4PM8FS KHS 1404968 PHOENIX CONTACT Sensor/actuator cable SAC-3PM12MS/4,0-PUR/4PM8FS KHS ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3PM12MS/4,0-PUR/4PM8FS KHS

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3PM12MS/4,0-PUR/4PM8FS KHS
Catalog number	1404968
Category	Data cable
Minimum order	50 Pcs
Document ID	EO-923A53C1A1
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-3PM12MS/4,0-PUR/4PM8FS KHS - 1404968
Sensor/actuator cable, halogen-free PUR, greyish black RAL 7021

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, PUR halogen-free, black-gray RAL 7021
Key Commercial Data
Orderkey 1404968
Packing unit 1
GTIN 4046356732376
Custom tariff number 85444290
General
Rated voltage 250 V AC
250 V DC
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
Length of twist, overall twist 40 mm
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 3.6 mm ±0.15 mm
Smallest bending radius, fixed installation 18 mm
Smallest bending radius, movable installation 36 mm
Number of bending cycles 10000000
Bending radius 44 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 18 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance >= 100 G?*km (at 20 °C)
Conductor resistance <= 78 ?/km (at 20 °C)
Nominal voltage, cable <= 300 V
Test voltage, cable >= 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Halogen-free in accordance with DIN VDE 0472 part 815
Resis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3PM12MS/4,0-PUR/4PM8FS KHS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.