INDUSTRIAL COMPONENT DATA

SAC-4P- 0,7-PUR/M12FR SORI 1534193 PHOENIX CONTACT Cable for sensors/actuators SAC-4P 0,7-PUR/M12FR SORI 153..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P- 0,7-PUR/M12FR SORI

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P- 0,7-PUR/M12FR SORI
Catalog number	1534193
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-53591B8244
Generated	2026-11-19

Product Overview

Cable for sensors/actuators - SAC-4P - 0,7-PUR/M12FR SORI - 1534193
Sensor/actuator cable, 4-pole, halogen-free, greyish-black RAL 7021, free cable end, to Elbow connection female M12, coding: A, cable length: 0.7 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators, 4-pole, PUR halogen-free, black-gray RAL 7021, end of free cable, to connection socket angled M12, coded, cable length: 0.7 m, a version of the client
Data commercial
Key order One million five hundred thirty four thousand one hundred ninety three
Packing unit 5 pcs
Key selling BF1CCA -
Minimum order quantity 5 pcs
EAN Four trillion seventeen billion nine hundred eighteen million nine hundred ninety three thousand six hundred thirty four
Unit weight (excluding packaging) 48,460 g
Measures
Cable length 0.7 m

Environmental conditions
Index of protection IP65
IP67
Overview
Current sizing at 40 °C 4 To
Tension sizing 250 V AC
250 V DC
Number of poles Four
Insulation resistance >= 10 M?
Encoding A - standard
Status indication Not
Category surge II
Pollution degree Three
Cycles of plug >= 100
Tightening torque 0.4 Nm
Material
Class of flammability according to UL 94 HB
Cable
Outer wrap, color black RAL 9005
Outer casing, material PUR
Room temperature (service) -25 °C ... 80 °C (cable, fixed)
-5 °C ... 80 °C (cable, available mobile)
Standards and specifications
Class of flammability according to UL 94 HB
Ratings
eCl@ss
eCl@ss 4.0 Twenty seven million sixty thousand three hundred six
eCl@ss 4.1 Twenty seven million sixty thousand three hundred six
eCl@ss 5.0 Twenty seven million sixty one thousand eight hundred one
eCl@ss 5.1 Twenty seven million sixty one thousand eight hundred
eCl@ss 6.0 Twenty seven million two hundred seventy nine thousand two hundred...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P- 0,7-PUR/M12FR SORI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.