INDUSTRIAL COMPONENT DATA

SAC-4P-0,80-PUR/8P-M12FS SH SO 1403159 PHOENIX CONTACT Sensor/actuator cable SAC-4P-0,80-PUR/8P-M12FS SH SO ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-0,80-PUR/8P-M12FS SH SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-0,80-PUR/8P-M12FS SH SO
Catalog number	1403159
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3101047501
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-4P-0,80-PUR/8P-M12FS SH SO - 1403159
Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, to straight female M12, cable length: 0.8 m, 8-pole female connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, shielded, free cable end, on Socket straight M12, cable length: 0.8 m, Socket is 8-pos.
Key Commercial Data
Orderkey 1403159
Packing unit 1
GTIN 4046356640695
Custom tariff number 85444290
Dimensions
Length of cable 0.8 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 2 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Pin assignment
Contact | Color (signal designation) | Contact (optional) 1 | BK
2 (not connected)
3 | BN
4 (not connected)
5 | BU
6 (not connected)
7 (not connected)
8 | WH
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y-V1-C-V1-11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 4x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-0,80-PUR/8P-M12FS SH SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.