INDUSTRIAL COMPONENT DATA

SAC-4P-100,0-BF145 1410758 PHOENIX CONTACT Cable ring, BETAflam 145, black, 4-pos., cable length: 100 m

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-100,0-BF145



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-100,0-BF145
Catalog number	1410758
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-4BC6946087
Generated	2026-11-19

Product Overview

Cable ring, BETAflam 145, black, 4-pos., cable length: 100 m
By meters, Cable ring, halogen-free POC, black RAL 9005, 4-conductors, color individual conductors: black 1, black 2, black 3, black 4, cross-linked by irradiation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1410758
Packing unit 1
GTIN 4046356906852
Custom tariff number 85444995
General
Environmental Product Compliance
Cable
Classifications
General
Rated voltage 250 V AC
250 V DC
Number of positions 4

Back to topCable
Cable type POC irradiated halogen-free black
Cable type (abbreviation) BF 145
Conductor cross section 4x 0.75 mm²
AWG signal line 18
Core diameter including insulation 2.2 mm
Wire colors black 1, black 2, black 3, black 4
Overall twist 4 wires around filler to the core
External sheath, color black RAL 9005
External cable diameter D 6.9 mm
Minimum bending radius, fixed installation 4 x D
Minimum bending radius, flexible installation 8 x D
Cable weight 75 kg/km
Outer sheath, material POC
Material conductor insulation POC
Conductor material Tin-plated Cu litz wires
Nominal voltage, cable 300 V
Test voltage, cable 3500 V
Special properties Irradiated
Flame resistance according to IEC 60332-1
according to EN 50265-2-1
Halogen-free according to IEC 60754-1
According to EN 50267-2-1
Concentration of fumes in accordance with IEC 61034
EN 50268-2
Ambient temperature (operation) -55 °C ... 145 °C (cable, fixed installation)
-35 °C ... 120 °C (cable, flexible installation)
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27060300
eCl@ss 4.1 27060300
eCl@ss 5.0 27061800
eCl@ss 5.1 27061800
eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-100,0-BF145 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.