INDUSTRIAL COMPONENT DATA

SAC-4P-15,0-600/M12FS FB 1425355 PHOENIX CONTACT Sensor/actuator cable SAC-4P-15,0-600/M12FS FB 1425355

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-15,0-600/M12FS FB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-15,0-600/M12FS FB
Catalog number	1425355
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-D1E6BE8743
Generated	2026-11-19

Product Overview

Sensor/actuator cable - SAC-4P-15,0-600/M12FS FB - 1425355
Sensor/actuator cable, 4-pole, PP-EPDM, grey RAL 7035, free cable end, to Straight connection female M12, coding: A, cable length: 15 m, Hygienic design, with plastic knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 4-position, PP-EPDM halogen-free, gray RAL 7035, free cable end, on Socket straight M12, A-coded, cable length: 15 m, Hygienic design, with plastic knurl
Key Commercial Data
Orderkey 1425355
Packing unit 1
GTIN 4055626394602
Custom tariff number 85444290
Dimensions
Length of cable 15 m
Ambient conditions
Degree of protection IP65
IP67
General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Material conformance FDA 21 CFR 177.2600
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Polypropylene
Sealing material FKM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Material conformance
Standards/regulations FDA 21 CFR 177.2600
Cable
Cable type Halogen-free PP gray
Cable type (abbreviation) 600
Cable abbreviation Li9Y9Y
Conductor cross section 4x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Length of twist, overall twist 48 mm
External s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-15,0-600/M12FS FB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.