INDUSTRIAL COMPONENT DATA

SAC-4P-15,0-PUR/M12FRS PE 1421535 PHOENIX CONTACT Power cable SAC-4P-15,0-PUR/M12FRS PE 1421535

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-15,0-PUR/M12FRS PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-15,0-PUR/M12FRS PE
Catalog number	1421535
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-E2E3D65695
Generated	2026-11-19

Product Overview

Power cable - SAC-4P-15,0-PUR/M12FRS PE - 1421535
Power cable, 4-pole halogen-free, free cable end, to Elbow Female M12, coding: S, cable length: 15 m, for alternating current up to 12 A/690 V
Power cable, 4-pin, halogen-free, grey-black RAL 7021, free conductor end, on M12 angled socket, coded: S, cable length: 15 m, for alternating current up to 12 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, S-coded, cable length: 15 m, for AC current up to 12 A/690 V
Key Commercial Data
Orderkey 1421535
Packing unit 1
GTIN 4055626269542
Custom tariff number 85444290
Dimensions
Length of cable 15 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 12 A
Rated voltage 690 V AC
Number of positions 4
Color handle area black
Insulation resistance >= 100 M?
Coding S power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PA
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-111
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9YV1-11Y
UL AWM style 20234 / 10492 (80°C/1000 V)
Conductor cross section 4x 1.5 mm²
AWG power supply 16
Conductor structure, voltage supply 78x 0.15 mm
Core diameter including insulation 2.45 mm ±0.05 mm
Thickness, insulation >= 0.36 mm
Wire colors Black 1, black 2, black 3, green/yel...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-15,0-PUR/M12FRS PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.