INDUSTRIAL COMPONENT DATA

SAC-4P- 2,0-600/M12FS FB 1420458 PHOENIX CONTACT Cable for sensors/actuators SAC-4P- 2,0-600/M12FS FB 1420458

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-2,0-600/M12FS FB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-2,0-600/M12FS FB
Catalog number	1420458
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3AF2FB1FC5
Generated	2026-11-19

Product Overview

Cable for sensors/actuators - SAC-4P- 2,0-600/M12FS FB - 1420458
Sensor/actuator cable, 4-pole, PP-EPDM, grey RAL 7035, free cable end and straight connection female M12, cable length: 2 m, Hygienic design, with plastic knurling
Sensor/actuator cable, 4-pin, PP-EPDM, grey RAL 7035, free conductor end, on M12 straight socket, coding: A, cable length: 2 m, Hygienic Design, with plastic ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensors/actuators, 4-pole, PP-EPDM halogen-free, gray RAL 7035, cable length: 2 m, hygienic Design, with knurled plastic
Data commercial
Key order One million four hundred twenty thousand four hundred fifty eight
Packing unit 1 pcs
Key selling BF1CCA -
Minimum order quantity 100 pcs
EAN Four trillion fifty five billion six hundred twenty six million two hundred seventeen thousand seven hundred eighty nine
Unit weight (excluding packaging) 62,000 g

Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety
Country of origin PL (Poland)
Measures
Cable length 2 m
Environmental conditions
Index of protection IP65
IP67
Overview
Current sizing at 40 °C 4 To
Tension sizing 250 V AC
250 V DC
Number of poles Four
Encoding A - standard
Standards/specifications Plug-in connector M12 to IEC 61076-2-101
Conformity of the material to FDA 21 CFR 177.2600
Status indication Not
Protective circuit/component protection without connect
Category surge II
Pollution degree Three
Tightening torque 0.4 Nm
Material
Material contact CuSn
Material contact surface Ni/Au
Material support of contacts PP
Material body grip PP
Material knurled Polypropylene
Material of the board FKM
Standards and specifications
Name of standard Plug-in connector M12
Standards/specifications IEC 61076-2-101
Name of standard Compliance of the material
Standards/specifications FDA 21 CFR 177.2600
Cable
Type of cable PP halogen-free, grey
Cable type (abbreviation) Six hundred
Abbrevia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-2,0-600/M12FS FB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.