INDUSTRIAL COMPONENT DATA

SAC-4P-30,0-PUR/M12FR-V2A 1512885 PHOENIX CONTACT Cable for sensors/actuators

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-30,0-PUR/M12FR-V2A

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-30,0-PUR/M12FR-V2A
Catalog number	1512885
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-58501EDC1E
Generated	2026-11-19

Product Overview

Cable for sensors/actuators
Sensor/actuator cable, halogen-free PUR, greyish black RAL 7021, cable length: 30 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable, sensor/actuator, INTERLOCK-free, halogen-free, black-gray RAL 7021, cable length: 30 m
Business
The code of the application One million five hundred twelve thousand eight hundred eighty five
The amount of the package (C#) 5 Pcs
The minimum quantity of the order 50 Pcs
Note The production is linked to the application (no removal)
GTIN Four trillion seventeen billion nine hundred eighteen million nine hundred ten thousand four hundred thirty three
Weight per piece (excluding packing) 880,000 GRM
The number of corporate and commercial Eighty five million four hundred forty four thousand two hundred ninety
The country-of-origin IN Germany
Measures
The length of the cable (30 m)
The general
Rated voltage 24 V DC

Mating cycles That is > 100
The line
The type of cable PUR halogen-free black
Cable type (code) PURE
The code for the cable Li9Y11Y-HF
The style of the UL AWM 20549 / 10493 (80 °C / 300 V)
The value of the driver 4x 0.34 mm2
The line of the signal WIRE Twenty two
The mounting of the conductive signal line on the 42x 0.10 mm
The diameter of the conductor, including the insulation In (1.27 mm ±0.02 mm
The density of the wall insulation >= 0.21 mm
The color of the driver brown, black, blue, brown, black
Stranded in total 4 conductors twisted together along
Outer shell, color the black-gray RAL 7021
The thickness of the wall of outer Jacket ca. 0.5 mm
The outer diameter of the cable D More than 4.2 mm (±0.15 mm)
Minimum bend radius of, the position of the fixed 5 x D
Mi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-30,0-PUR/M12FR-V2A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.