INDUSTRIAL COMPONENT DATA

# SAC-4P- 5,0-110/M12FRT 1089984 PHOENIX CONTACT Power cable, 4-position, PVC, black-gray RAL 7021, Socket ang..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-5,0-110/M12FRT**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SAC-4P-5,0-110/M12FRT |
| Catalog number | 1089984 |
| Category | Sensor-actuator patch cord |
| Minimum order | 1 Pcs |
| Document ID | EO-452F567BBC |
| Generated | 2026-11-19 |

## Product Overview

Power cable, 4-position, PVC, black-gray RAL 7021, Socket angled M12, on free cable end, cable length: 5 m, For direct current up to 12 A/63 V
Power cable, 4-pole, free cable end, to Elbow Female M12, coding: T, cable length: 5 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |

## Additional Product Information

Key Commercial Data
Orderkey 1089984
Packing unit 1 pc
Catalog page Page 291 (C-2-2019)
GTIN 4055626898629
Weight per Piece (excluding packing) 540.000 g
Custom tariff number 85444290
Country of origin PL (Poland)
Drawings
Ambient conditions
Material
Cable
Classifications

Dimensions
General
Standards and Regulations
Environmental Product Compliance
Drawings
Dimensional drawing
M12 x 1 socket, angled
Circuit diagram
Contact assignment of the M12 socket
Schematic diagram
Pin assignment of M12 socket, 4-pos., T-coded, socket side view
Cable cross section
PVC black [110]
Back to topDimensions
Length of cable 5 m
Back to topAmbient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP65
IP67
Back to topGeneral
Rated current at 40°C 12 A
Rated voltage 63 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding T power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Back to topMaterial
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PP
Material, knurls Zinc die-cast, nickel-plated
Back to topStandards and Regulations
Standards/specifications M12 connector IEC 61076-2-111
Flammability rating according to UL 94 V0
Back to topCable
Cable type PVC black
Cable type (abbreviation) 110
UL AWM style 2023...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-5,0-110/M12FRT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.