INDUSTRIAL COMPONENT DATA

SAC-4P-500,0-PUR/SH-0,25 1403861 PHOENIX CONTACT Cable reel SAC-4P-500,0-PUR/SH-0,25 1403861

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-500,0-PUR/SH-0,25

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-500,0-PUR/SH-0,25
Catalog number	1403861
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-870302FA13
Generated	2026-11-19

Product Overview

Cable reel - SAC-4P-500,0-PUR/SH-0,25 - 1403861
By the meter, Cable reel, shielded, PUR halogen-free, black-gray RAL 7021, 4-wire, color single wire: brown, white, blue, black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Cable by the meter
Cable/linePUR halogen-free black [PUR]
Dimensional drawing
Cable weight 31 kg/km
UL AWM Style 20549
Number of positions 4
Shielded yes
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 4x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm ±0.02 mm (Signal line)
External cable diameter 4.70 mm ±0.15 mm

Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation >= 0.21 mm (Core insulation)
approx. 0.50 mm (Outer cable sheath)
Overall twist 4 wires, twisted
Optical shield covering 80 %
Max. conductor resistance max. 78 ?/km (at 20 °C)
Insulation resistance >= 100 G?*km (at 20 °C)
Nominal voltage, cable <= 300 V
Test voltage >= 3000 V
Smallest bending radius, fixed installation 24 mm
Smallest bending radius, movable installation 48 mm
Dynamic load capacity (bending) Max. bending cycles: 10000000, Bending radius: 48 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s²
Halogen-free in accordance with DIN VDE 0472 part 815
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Resistance to oil in accordance with DIN EN 60811-2-1
Other resistance Highly resistant to acids, alkaline solutions and solvents
hydrolysis and microbe resistant
partly UV-resistan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-500,0-PUR/SH-0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.