INDUSTRIAL COMPONENT DATA

SAC-4P-20,0-PUR/M12FST SH 1415343 PHOENIX CONTACT Power cable SAC-4P-20,0-PUR/M12FST SH 1415343

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-20,0-PUR/M12FST SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-20,0-PUR/M12FST SH
Catalog number	1415343
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-4D64493733
Generated	2026-11-19

Product Overview

Power cable - SAC-4P-20,0-PUR/M12FST SH - 1415343
Power cable, 4-pole halogen-free, shielded (Advanced Shielding Technology), free cable end, to straight female M12, coding: T, cable length: 20 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Power cable, 4-position, PUR halogen-free, black RAL 9005, shielded (Advanced Shielding Technology), free cable end, on Socket straight M12, T-coded, cable length: 20 m
Key Commercial Data
Orderkey 1415343
Packing unit 1
GTIN 4055626046907
Custom tariff number 85444290
Dimensions
Length of cable 20 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
0 °C ... 55 °C (Temperature range in accordance with GL)
Degree of protection IP65

IP67
General
Rated current at 40°C 12 A
Rated voltage 63 V DC
Number of positions 4
Color handle area black
Insulation resistance >= 100 M?
Coding T power
Standards/regulations M12 connector IEC 61076-2-111
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PA
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-111
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LS9YC11Y-OB
Conductor cross section 4x 1.5 mm²
AWG power supply 16
Core diameter including insulation 2.4 mm
Thickness, insulation 1.2 mm (Outer cable sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires optima...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-20,0-PUR/M12FST SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.