INDUSTRIAL COMPONENT DATA

SAC-4P-M 8MS/0,27-PUR 08 SHOBS 1444296 PHOENIX CONTACT Cable for sensors/actuators, 4-pole, PUR halogen-free..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M 8MS/0,27-PUR 08 SHOBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M 8MS/0,27-PUR 08 SHOBS
Catalog number	1444296
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B641B9A2E2
Generated	2026-11-19

Product Overview

Cable for sensors/actuators, 4-pole, PUR halogen-free, black-gray RAL 7021, shielded, male Connector straight M8, to end of free cable, cable length: 0,27 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cables for sensors/actuators, 4-pin, PUR, free of halogen, grey-black RAL 7021, shielded, Plug straight M8, on free end, length of cable: 0.27 m
Trade data
Order Code One million four hundred forty four thousand two hundred ninety six
Packaging unit One
GTIN Four trillion forty six billion three hundred fifty six million five hundred twenty six thousand two hundred twenty seven
Number of the customs tariff Eighty five million four hundred forty four thousand two hundred ninety
Ratings
Cable length 0.27 m
Lengths of the decladding of the end is not completed 80 mm
Environmental Conditions
Index of protection IP65

IP67
General
Reference current at 40 °C Four
Reference voltage 48 V AC
60 V DC
Number of poles Four
Insulation resistance >= 100 M?
Tamperproof A - standard
Status display Not
Overvoltage category II
Pollution degree Three
Material
Flammability class according to UL 94 HB
Contact material CuSn
Material of contact surface Ni/Au
Material of door-contacts TPU GF
Material of grip surface TPU, flame-retardant, self-extinguishing
Material of the wheel Zinc die-cast, nickel-plated
Standards and specifications
Flammability class according to UL 94 HB
Cable
Type of cable PURE free halogen black
Cable Type (symbol) PURE
Symbol cable LiF9YC11Y
Style UL AWM Twenty thousand five hundred forty nine
Cross Section of the conductor 4x 0.25 mm2 (signal Line)
AWG line signals Twenty four
Structure of the driver signal line 32x 0.10 mm
Diameter of wire with insulation 1.17 mm ±0.02 mm (si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M 8MS/0,27-PUR 08 SHOBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.