INDUSTRIAL COMPONENT DATA

SAC-4P-M12MRDC5/ 2,0-93E/RJ45 1405185 PHOENIX CONTACT Network cable SAC-4P-M12MRDC5/ 2,0-93E/RJ45 1405185

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MRDC5/ 2,0-93E/RJ45



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MRDC5/ 2,0-93E/RJ45
Catalog number	1405185
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-54F2F734C8
Generated	2026-11-19

Product Overview

Network cable - SAC-4P-M12MRDC5/ 2,0-93E/RJ45 - 1405185
Network cable, CAT5 Ethernet, 4-pole, PUR, water blue RAL 5021, shielded, Angled connector M12 / IP67, coding: D, a Straight RJ45 / IP20 connector, cable length: 2 m, C5 output direction, 315° coding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Network cable, Ethernet CAT5, 4-position, PUR, water blue RAL 5021, shielded, Plug angled M12 / IP67, coding: D, on Plug straight RJ45 / IP20, cable length: 2 m, Outlet direction C5, 315° coding
Key Commercial Data
Orderkey 1405185
Packing unit 1
GTIN 4046356737319
Custom tariff number 85444290
Dimensions
Length of cable 2 m
Ambient conditions
Degree of protection IP65 (M12 connector)

IP67 (M12 connector)
IP20 (RJ45 connector)
General data
Rated current at 40°C 1 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category Ethernet CAT5 (IEC 11801:2002)
Standards/regulations M12 connector IEC 61076-2-101
Characteristics head 1
Head type Plug angled M12 / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuZn (Contact)
Ni/Au (Contact surface)
TPU (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Shielded yes
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Characteristics head 2
Head type Plug straight RJ45 / IP20
No. of positions (pin connector pattern) 4 (8)
Color gray
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PC (Contact carriers)
PA (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -40 °C ... 60 °C
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Cable
Cable type PUR ETHERNET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MRDC5/ 2,0-93E/RJ45 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.