INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 0,3-PUR 1530142 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 0,3-PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 0,3-PUR
Catalog number	1530142
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-0C94ED7BDA
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, halogen-free PUR, grayish black RAL 7021, Straight male connector M12, coding: A, to free cable end, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1530142
Packing unit 5 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4017918989880
Weight per Piece (excluding packing) 19.500 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.3 m
Stripping length of the free conductor end 50 mm
Ambient conditions

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 4.2 mm ±0.15 mm
Minimum bending radius, fixed inst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 0,3-PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.